


# 3M<sup>™</sup> Digital Projector X76

Ideal for larger conference rooms, boardrooms, training rooms and classrooms the 3M Digital Projector X76 delivers impressive brightness with its powerful 3500 lumens and crisp video and data image display for multimedia and multi-purpose environments. Advanced features like automatic vertical keystone adjustment and personalized settings make the 3M X76 a great tool for presenting a professional image.



# **Features**

- XGA (1024 x 768) resolution
- 3500 lumens\*
- 7.7 lbs. (3.5kg)
- Automatic Vertical Keystone
- HDTV compatible
- 7W audio output
- Full connectivity
- USB for remote mouse control
- 1–RGB/Computer/Output ideal for a teacher's monitor
- 3-year standard warranty \*Indicates maximum lumens rating





# Optical

Resolution Native: true XGA (1024 x 768) Maximum: UXGA (1600 x 1200)

Imager set 0.63", P-Si TFT Panel

#### Aspect Ratio 4:3 native and 16:9 letterbox supported Colors

16.7 million **Contrast Ratio** 500:1

Brightness 3500 lumens (maximum rating) **Projection Lens** 

F1.6-1.8 (f=18.9-22.6mm) Vertical Lens Shift

9:1 (fixed) Throw Ratio (Distance: Image Width) 1.5:1 - 1.7:1

Screen Size (range) 30-300 inches

Zoom/Focus Manual

Zoom Ratio

1.2:1 **Optional Lenses** N/A Lamp

UHB 230W (normal mode), 170W (whisper mode) Lamp Life

2000 hours (normal mode) Up to 3000 hours (whisper mode)

## Size

Dimensions (W x H x D) 13.4 x 3.94 x 10.6 in. (340 x 100 x 270mm) Weight 7.8 lbs (3.5kg)

#### Warranties

For details see www.3m.com/meetings/warrantie Projector

3 years or 2500 hours

Lamp

90 days or 180 hours with remainder of year 1 Ultra Value Warranty Enhancement (op

Includes 1 free lamp, free loaner while unit is being repaired and expedited service. Not available outside U.S.

#### System Specifications Video Compatibility

NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM SDTV/HDTV 525i(480i), 525p(480p), 625i (576i)/ 750p(720p@60Hz), 1125i(1080i@60Hz)

**Close Caption** CC1-4, TEXT1-4 (NTSC only) **Digital Keystone Correction** 

Vertical ±30 degrees

Audio Output 7 Watt Startup Screen Customizable Noise Level Normal 36dB: Whisper 30dB

**Horizontal Scan** 31.5-106kHz Vertical Scan 56-120Hz

# Power Consumption

320W (during operation); 5W (standby mode set to saving\*) \*All RS-232 functions are disabled except Turn On. The Monitor Out and Audio Out are disabled.

Power Supply Universal: 100-120V/220-240V, 50/60Hz

**Regulatory Approvals** UL, cUL, FCC Part 15 -Class B, CE, EN60950 **Operating Temperature** 

41°-95°F (5°-35°C)

Storage Temperature -4°- 140°F (-20°- 60°C)

Altitude Sea level to 6000 ft. (1,829m)

### Technical Support

· Free unlimited software downloads and updates available on our website at www.3m.com/meetings

24/7 Technical Support by calling 800.328.1371

Connections C

Computer	
Computer In1, In2	15 Pin HD - Sub-analog computer input
USB	USB Type A-Mouse Emulation
RGB Output	15 Pin HD-Sub-analog computer output*
Control	9 Pin D-RS232 control port
Audio In 1,2	3.5mm stereo mini jack - PC audio input
Audio Out	3.5mm stereo mini jack - computer and
	video audio output
Video	
Component	3xRCA (Y, Cb/Pb, Cr/Pr)–Component
	Video input
S-Video	4 Pin Mini-Din-S-Video input
Video	RCA-Composite Video input
AUDIO IN 3	2xRCA (Red, White) - right and left channel

# Accessories Included

Power cords (US, UK, Europe) Remote control Lens cap Soft case VGA cable RCA Video/Audio cable RCA Component cable USB cable

## **Optional Accessories**

Ultra Value Enhanced Warranty	
(X76) U.S. only	78-6969-9945-3
Lamp replacement kit (X76)	78-6969-9947-9
Ceiling mount	78-6969-9860-4

audio input

ties	Screen Size Diagonal [inch (m)]	Image Size 4:3 Projection Distance Min. [inch (m)] Max. [inch (m)]		Image Size 16:9 Projection Distance Min. [inch (m)] Max. [inch (m)]	
100	40" (1.0)	46" (1.2)	56" (1.4)	50" (1.3)	61" (1.5)
	60" (1.5)	70" (1.8)	84" (2.1)	76" (1.9)	91" (2.3)
o vo vo to d	100" (2.5)	117" (3.0)	140" (3.6)	127" (3.2)	153" (3.9)
prorated <b>ptional)</b>	150" (3.8)	176" (4.5)	211" (5.4)	192" (4.9)	230" (5.8)
puondi)	200" (5.1)	235" (6.0)	282" (7.2)	256" (6.5)	307" (7.8)
	300" (7.6)	352" (9.0)	423" (10.8)	384" (9.8)	461" (11.7)

Note: These sizes are ±10 percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

### 800.328.1371 | www.3m.com/meetings

#### Specifications subject to change without notice.

Hg-LAMP CONTAINS MERCURY. Manage in accordance with disposal laws. See www.lamprecycle. org or call 1-800-328-1371(USA), 1-800-364-3577 (Canada). For product disposal see www.eiae.org (USA) or www.epsc.ca (Canada).

# **3M Projection**

Systems Building A147-5N-01 6801 River Place Blvd. Austin, TX 78726-9000 USA

#### **3M Canada** 3M Mexico, S.A. de C.V. PO Box 5757 Apartado Postal 14-139 Ontario, Canada

Mexico, D.F. 07070 Mexico

London.

NGA 4T1

Printed in USA v03 08

#### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of 3 years from the time of purchase, 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M, and the 3M logo are trademarks of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.