



Professional-Grade XGA DLP® Multimedia Projector for the Large Venue Marketplace

The Vivitek D5000 XGA digital projector utilizes the latest advancements in video processing technologies to create remarkable image quality. A professional-grade projector with the large venue marketplace in mind, the D5000 delivers amazing video performance. With manual lens shift functions and multiple connectivity alternatives, the Vivitek D5000 is the most comprehensive projector to create a superior picture in a large venue environment.

Features

- 5200 lumens and 2500:1 contrast ratio
- 3D-ready with DLP® Link™
- DLP® and BrilliantColor™ technologies from Texas Instruments
- 3 interchangeable lens options and manual lens shift (vertical/horizontal) for easy setup
- Connectivity options include: HDMI v1.3, DVI-D, VGA-In, BNC, Component, S-Video, Composite
- RS-232c for one-touch automation and 12V trigger for simple screen/projector automation functionality

Specifications	
Brightness	5200 Lumens (Typical)
Native Resolution	XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2500:1 (Full On/Full Off)
Lamp Life and Type	≈2000/1500 Hours (Standard/Boost Mode), 380W UHP
Lamp Part #	TBA
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	1.6 to 2.0:1 (Distance/Width)
Image Size (Diagonal)	37" to 215"
Projection Distance	4.92' to 23'
Projection Lens	F=2.46 - 2.56, f=22.82 - 28.49 mm
Zoom Ratio	1.25:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Keystone Correction	±30° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	50 to 85 Hz
Speakers Output	6 Watts (3W Mono x2)
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Lens Shift Range	Vertical: ±100%, Horizontal: -10% to +110%
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3, DVI-D, VGA-In (x2), VGA-Out, BNC, Component Video, S-Video, Composite Video, RCA Audio-In (x2), Mni-jack Audio (x3), 12V Trigger (x2), RS-232c, RJ45, USB (Service Only)
Security	Kensington® Lock Port, Security Bar
Weight	19 lbs (8.6 kg)
Dimensions (W x H x D)	17.0" x 7.1" x 13.5" (431 x 180 x 343 mm)
Noise Level	37dB/33dB (Boost/Standard Mode)
Power	Supply: AC 100-240V, 50 / 60Hz Consumption: 335W (Standard Mode), 390W (Boost Mode), <1W (Standby)
Operating Temperature	41 to 104°F (5 to 40°C), 80% Max Humidity
Warranty	1-Year Limited Warranty, 90-Day Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card
Optional Accessories	Standard Lens, Fixed Short Throw Lens, Long Throw Lens, Replacement Lamp/Remote
UPC	8 14964 33525 8

