

Bright and Lightweight, HD- and 3D-Ready

With a brightness level up to 300 lumens and weighing only 1.4 pounds, the Qumi is Vivitek's innovative LED pocket projector. The Qumi features a DLP® Pico chipset and BrilliantColor™ technologies from Texas Instruments. It is also the first pocket projector to be 3D-ready via DLP Link™. The Qumi's sleek design and connectivity options allows it to be used with a variety of devices, including, but not limited to smart phones, laptops, netbooks and tablets, digital and video cameras. Versatile and portable, the Vivitek Qumi is perfect for sharing digital content at work and play.

Features

- Native 720p HD/WXGA (1280x800) resolution
- Up to 300 lumens of brightness
- Estimated 30,000 hours of operation
- USB and MicroSD slots for content and memory expansion
- 3D-Ready via DLP Link
- Connectivity options: Mini-HDMI, Universal I/O, 3.5mm video-in, 3.5mm mini-jack audio-out
- Only 1.4 pounds and available in black or white finish



Specifications	
Brightness	300 Lumens (Typical)
Native Resolution	720p HD/WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2,500:1 (Full On/Full Off)
Lamp Life and Type	≈30,000 Hours, LED
Display Type	Single Pico DLP® Technology by Texas Instruments
Throw Ratio	1.55:1 (Distance/Width)
Image Size (Diagonal)	30" to 90" (0.8 to 2.3 m)
Projection Distance	3.28' to 9.84' (1 to 3m)
Projection Lens	TBD
Zoom Ratio	Fixed Lens
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Offset	102.5%
Keystone Correction	± 15° Vertical (± 30 Step)
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	1W Mono
Projection Method	Table Top or Tripod (Front or Rear)
Uniformity	85%
File Compatibility	JPEG, Mpeg 4, H.264, Office Viewer
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	Mini-HDMI, Universal I/O (24-Pin Connector for VGA/Component Input), 3.5mm Video-In, 3.5mm Mini-Jack Audio-Out, USB, MicroSD
Weight	21.7 oz (1.4 lbs)
Dimensions (W x H x D)	6.3" x 1.3" x 4.0" (162 x 32 x 102 mm)
Noise Level	28dB/32dB (Standard / Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 85W (Boost Mode), <0.5W (Standby)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	1-Year Limited Parts and Labor
Standard Accessories	Power Adapter, Universal I/O to VGA Cable, 30-pin connector to HDMI v1.3 Cable, Mini-HDMI to HDMI Cable, Mini-Jack to SD AV Cable, Carrying Case, Remote Control, Warranty Card
Optional Accessories	Carrying Case, Qumi Battery Dock, Protective Rubber Case, External Speakers
UPC	8 14964 33591 3 (White), 8 14964 33569 2 (Black)

