

3,000 LUMENS ● XGA ● ULTRAPORTABLE PROJECTOR

PLC-XW300

ULTRAPORTABLE PROJECTOR



3LCD



Built-in Network



Closed Caption

ULTRA-COMPACT, FULLY PORTABLE XGA DESIGN

Not much larger than a laptop PC, the PLC-XW300 weighs less than 5.5 pounds and delivers true XGA picture quality in a versatile, go anywhere system. Also the PLC-XW300 may be mounted ceiling or inverse for enhanced versatility.

COMPLETE EASY AUTO SET UP FUNCTION, SMART AUTO INPUT SEARCH AND AUTO VERTICAL KEYSTONE CORRECTION

PLC-XW300 provides "Auto Set Up Function" that corrects keystone shaped distortion by searching for an input signal and detecting projector incline, therefore reducing set up time. PLC-XW300 automatically compensates for keystone picture distortion. Auto Keystone Correction, Auto Input Search and Auto PC Adjustment make it a easy to use smart projector.

WIRED LAN (RJ-45) FOR NETWORK PROJECTOR CONTROL

This model is equipped with Wired LAN (RJ-45) that allows you to manage and control the projector via Network. It is possible to check the operating time of lamp and manage the warning notification by email. Power ON/OFF and switching of the input signal can be controlled.

DUAL D-SUB15 INPUTS

The PLC-XW300 offers excellent flexibility via a pair of D-Sub15 RGB input terminals. Using an optional adapter cable, it can even accept component video signals. One of the D-Sub15 terminals can even be switched between input and monitor output for greater programming flexibility.

BLACK BOARD / COLOR BOARD MODE

The PLCX-W300 is compatible with four variously colored (red, blue, green, and yellow) projection surfaces via 'Color Board Mode' without a screen.

CLOSED CAPTION

PLC-XW300 is Closed Caption compatible.

Resolution	XGA (1024 x 768)	
Brightness (typical)	3,000 Lm	
Contrast Ratio (Full on / off)	500:1	
Image Size	40"-300"	
Aspect Ratio	4:3	
Projection Lamp	220W	
Scanning Frequency	H:15-100kHz, V:50-100Hz	
Fan Noise	29 dBA (Eco)	
Voltage	100-240V AC (auto voltage) ; 50/60 Hz	
Power Consumption	212 W (Eco)	
Input signal compatibility	UXGA/ WXGA/ SXGA+/ SXGA/ XGA/ SVGA/ VGA/ MAC	
Color System	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N	
Projection Lens (inch)	F 2.00- 2.15 f=0.72" - 0.87"	
Throw Ratio	1.43 - 1.72 : 1	
Throw Distance (feet)	4.3' - 38.7'	
Zoom / Focus	Manual	
Up / Down Ratio	4.3 :1	
Digital Keystone Correction	V +/- 30° MAX	
Digital Zoom	16x - 1/4x	
Speaker Output	1W	
Weight (lbs)	5.5 lbs	
Dimensions (inch) W,H,D	13.1 x 3.4 x 9.7"	
Replacement Lamp	610 345 2456	
Replacement Remote	645 099 3213	
Lamp Life * (hours)	4000h (Eco)	
Input	PC/Video	D-sub 15 x1 (RGB, Monitor out) D-sub 15 x1 (RGB, Component, S-Video) RCA x1 (Composite)
	Audio	Stereo mini jack x 1
Output	PC/Video	D-sub 15 x1 (Monitor out)
	Audio	Stereo mini jack x 1
Other Feature	RJ-45 (LAN), Dsub 9pin (RS232C)	
Included Accessories	Power cord x 1 VGA cable x 1 Quick reference guide Owner's manual x 1(CD-ROM) Lens Cap x 1 Remote control x 1 (AAA Battery x 2) CD-ROM read me note CD-ROM (PJ-Net Manager application software) PIN code Label Lamp replacement label UL cable card Warranty card	
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty	

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.



PRESENTATION TECHNOLOGIES
21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax: 818-717-2719
www.sanyoprojectors.com



Back Panel